



Project Number: 3124129

Date Issued: 12/18/2009

Certificate of Conformance #: 3117361CRT-007

Test Report Number: 3124129CRT-023b

Applicant:

Superior Essex
Attn: Ms. Gayle Watson
6120 Powers Ferry Road
Suite 150
Atlanta, GA 30339

Manufacturer:

Leviton Network Solutions
Attn: Mr. Gary Bernstein
2222 222nd SE
Bothell, WA 98021



Dear Ms. Gayle Watson;

Intertek is pleased to provide this Letter Report covering the follow-up testing on your 4 Connector Channel. The sample were submitted from your Superior Essex's distribution located in Hoisington, KS and Leviton's distribution located in Bothell WA. The samples were received on 12/2/2009 in good condition for Quarter 4 2009 Follow-up Testing.

4 Connector Channel: Cat-5e+

Manufacturer	Part Number	Description
Leviton	5G460-XXL	Equipment Cord (XX denotes length)
Leviton	5G110-RL5	Wall Outlet
Superior Essex	52-200-X5-CMR	Cobra Horizontal Cable (X denotes color)
Leviton	41AB2-1F4	110 Block
Leviton	5G596-U24	Patch Panel
Leviton	5G460-XXL	Cross Connect (XX denotes length)

The testing was performed at Intertek located in Cortland, NY on 12/17/2009 to the ANSI/TIA-568-B.2 Category 5e and the NextLan Specification Rev. 5 and did comply with the applicable requirements of the test specifications.

We have appreciated this opportunity to be of service to you. If there are any questions regarding this letter or any other services offered by Intertek, please do not hesitate to contact us.

Sincerely,

Kathy Heath
Project Coordinator
Global Cabling Products Testing
Phone: (607) 758-6641
Email: kathy.heath@intertek.com


John Cash
Technician
Global Cabling Products Testing
Phone: (607) 758-6677
Email: john.cash@intertek.com

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.




Summary

Client	Superior Essex	Report No	3124129CRT-023b
Specification	Cat 5e Channel NextLAN S350 Limits 155MHz	Length	100.
Part No	52-200-25-CMR	Temperature	20 °C
Test Started	12/17/2009 10:49:04 AM	Test Status	Complies
Description	4 Connector Channel		A
Technician	John Cash		



Attenuation			
Freq	Worst Case	Average	Spec
1.	1.9	1.9	2.1
4.	3.8	3.8	4.2
8.	5.5	5.4	6.0
10.	6.1	6.1	6.7
16.	7.8	7.7	8.6
20.	8.8	8.7	9.6
25.	9.9	9.8	10.8
31.25	11.1	11.0	12.2
62.5	16.0	15.8	17.6
100.	20.5	20.2	22.8
250.	33.8	33.0	
350.	40.6	39.7	




Return Loss			
Freq	Worst Case	Average	Spec
1.	35.6	44.1	19.0
4.	41.9	49.4	19.0
8.	35.4	48.1	19.0
10.	38.2	45.8	19.0
16.	34.4	47.2	19.0
20.	35.2	51.3	19.0
25.	35.5	44.1	18.0
31.25	35.4	43.2	17.1
62.5	33.5	39.2	14.1
100.	28.9	37.4	12.0
250.	21.0	35.1	
350.	21.8	32.2	




Summary

Client	Superior Essex	Report No	3124129CRT-023b
Specification	Cat 5e Channel NextLAN S350 Limits 155MHz	Length	100.
Part No	52-200-25-CMR	Temperature	20 °C
Test Started	12/17/2009 10:49:04 AM	Test Status	Complies
Description	4 Connector Channel		A
Technician	John Cash		



NEXT			
Freq	Worst Case	Average	Spec
1.	76.1	84.2	64.1
4.	71.4	74.5	54.9
8.	63.2	68.1	49.9
10.	64.6	70.7	48.4
16.	57.8	65.2	45.0
20.	54.8	65.3	43.5
25.	53.8	61.0	41.9
31.25	53.3	60.7	40.3
62.5	45.9	55.5	34.9
100.	44.4	54.0	32.6
250.	40.5	46.4	
350.	35.5	43.6	




PSNEXT			
Freq	Worst Case	Average	Spec
1.	74.7	77.9	61.9
4.	67.3	69.0	52.3
8.	59.4	62.4	47.1
10.	60.5	64.5	45.5
16.	56.1	58.9	42.0
20.	53.6	59.0	40.4
25.	51.4	55.1	38.7
31.25	49.0	54.1	37.1
62.5	44.2	48.3	33.3
100.	42.9	46.9	31.9
250.	36.7	39.2	
350.	33.1	37.1	




Summary

Client	Superior Essex	Report No	3124129CRT-023b
Specification	Cat 5e Channel NextLAN S350 Limits 155MHz	Length	100.
Part No	52-200-25-CMR	Temperature	20 °C
Test Started	12/17/2009 10:49:04 AM		A
Description	4 Connector Channel	Test Status	Complies
Technician	John Cash		



ACR			
Freq	Worst Case	Average	Spec
1.	74.2	82.3	62.0
4.	67.6	70.7	50.7
8.	57.9	62.7	44.0
10.	58.6	64.7	41.7
16.	50.1	57.5	36.5
20.	46.0	56.7	33.8
25.	43.9	51.2	31.1
31.25	42.4	49.7	28.1
62.5	29.9	39.7	17.3
100.	24.5	33.8	9.8
250.	7.8	13.3	
350.	-5.1	4.0	




PSACR			
Freq	Worst Case	Average	Spec
1.	72.8	76.0	59.8
4.	63.5	65.2	48.1
8.	54.0	57.0	41.2
10.	54.6	58.5	38.8
16.	48.3	51.1	33.5
20.	44.8	50.3	30.8
25.	41.8	45.4	27.9
31.25	38.2	43.1	24.9
62.5	28.3	32.5	15.7
100.	22.5	26.7	9.1
250.	3.4	6.2	
350.	-7.4	-2.5	




Summary

Client	Superior Essex	Report No	3124129CRT-023b
Specification	Cat 5e Channel NextLAN S350 Limits 155MHz	Length	100.
Part No	52-200-25-CMR	Temperature	20 °C
Test Started	12/17/2009 10:49:04 AM	Test Status	Complies
Description	4 Connector Channel		
Technician	John Cash		



ELFEXT			
Freq	Worst Case	Average	Spec
1.	72.6	85.3	58.1
4.	60.5	72.7	47.0
8.	54.4	66.8	41.1
10.	53.0	65.7	39.2
16.	49.4	61.5	35.2
20.	47.7	60.1	33.3
25.	46.4	57.4	31.4
31.25	45.5	56.1	29.5
62.5	41.5	51.8	23.6
100.	31.1	47.9	19.6
250.	28.5	32.7	
350.	22.7	32.3	



PSELFEXT			
Freq	Worst Case	Average	Spec
1.	71.4	74.2	55.7
4.	59.8	62.3	44.4
8.	53.8	56.2	38.3
10.	52.1	54.7	36.4
16.	48.3	50.8	32.3
20.	46.9	49.1	30.4
25.	45.4	47.7	28.4
31.25	44.4	46.6	26.5
62.5	40.4	42.8	20.5
100.	31.0	37.5	16.4
250.	24.8	27.1	
350.	21.7	25.3	